



RAG Driveshaft USA CORP.

3SRS7GM+[33-300/1]LM THK Miniature Linear Guide Full Ball SRS-G Accuracy and Preload Selectable

Bearing No. 3SRS7GM+[33-300/1]LM

| | |
|--|------------------------------|
| Days to Ship | 27 Days |
| Block Type | [Standard] M: Compact |
| The number of LM blocks combined with a axis | 3 |
| Nominal Part Number | 7 |
| Rail Type | Standard |
| Rail Width W1 | 7 mm |
| Mounting Height M | 8 mm |
| Rail Length L | 33 ~ 300 mm |
| Radial Clearance | Normal |
| Accuracy Grade | Normal Grade (Best Leadtime) |
| Rolling Element | Ball |
| Basic Load Rating Dynamic Rating C(N) | 1160 |
| Basic Load Rating Static Rating Co(N) | 1540 |
| Allowable Static Moment MA(N m) | 3.61 |
| Allowable Static Moment MB(N m) | 4.14 |
| Allowable Static Moment MC(N m) | 6.57 |
| Symbols for Dust Resistance | None (Not Recommended) |
| Block external dimension W | 17 mm |
| Block external dimension L | 23.4 mm |
| | |

3SRS7GM+[33-300/1]LM Bearing 2D drawings and 3D CAD models



RAG Driveshaft USA CORP.

| | |
|---------------------------------------|---------|
| Number of Block Mounting Holes(holes) | 4 |
| Mounting Hole Dimension S(M) | M2 |
| Mounting Hole Screw Depth | 2.3 mm |
| Block dimension L1 | 13.4 mm |